



Fastest 3/8 in. air ratchet in the West...East, North, and South

FAR7000

High Speed, Low Torque 3/8 In. Drive Air Ratchet

Features and Benefits

- FAST — 410 RPM free speed for fast removal/installation
- Slim drive head combined with a long reach—11.2 inches overall length—makes getting into tight spots easy
- Adjustable exhaust deflector directs exhaust away from the work area
- Lightweight—just 2.08 pounds—combined with the ergonomic comfort grip handle reduces fatigue
- Maximum torque of 30 foot-pounds won't strip threads
- 2.6 CFM air consumption
- Similar to the former FAR70C model



WARNING



• Power tools can cause flying particles
Wear safety goggles (Users and bystanders)

Flying particles can cause injury



• Power tools generate noise
Wear hearing protection (Users and bystanders).

Prolonged exposure to noise can cause hearing loss.



• Power tools vibrate

Avoid prolonged exposure to vibration.

Prolonged exposure to vibration can cause injury.


• Improper use of power tools and accessories can cause broken tools.
Do not use without all guards in place.

Use accessories rated at tool RPM.

Read and follow instructions before using power tools.

Broken tools can cause injury.

Read additional safety precautions on pages W1 to W4 in product catalog CAT1200.





FAR7000

Comparison Chart *

Brand	Snap-on	Matco	Matco	Ingersoll Rand	Mac Tools	Mac Tools	Mac Tools
Model	FAR 7000	MT2838	MT1840	IR1105max-D3	ARP 138	ARQP 380M	AR 7762A
	High RPM/Low Torque	Compact Ratchet	Mini Ratchet	Mini Ratchet	Palm Ratchet	Mini, Low Noise	Mini Ratchet
Air Pressure, psig (kPa)	90 (620)	90 (620)	92 (620)	93 (620)	90 (620)	90 (620)	90 (620)
CFM [l/min]	2.6 (18)	4	2.5	4.0	2.4	4	2.8
Free Speed, RPM	410	270	240	270	220	200	250
Sound Level, free speed, dBa	91.4	87	82	86.6	92.5	80	82.7
Torque Range, ft. lb. (N•m)	30 ft. lbs.	45	30	25	20	20	25
Air Inlet Thread Size	1/4 in.-18 NPT	1/4 in.-18 NPT	1/4 in.-18 NPT	1/4 in.-18 NPT	1/4 in.-18 NPT	1/4 in.-18 NPT	1/4 in.-18 NPT
Hose Inner Dia., in. (mm)	3/8 (10) ID min.	3/8 (10) ID min.	3/8 (10) ID min.	3/8 (10) ID min.	3/8 (10) ID min.	3/8 (10) ID min.	3/8 (10) ID min.
Overall Length, in. (mm)	11.2 (284.5)	12.45 (316.2)	6.7 (170.2)	7.5 (190.5)	5 (127)	7.7 (195.6)	7.75 (196.9)
Weight, lbs. (kg)	2.08 lbs. (0.94)	1.8 (0.81)	1.1 lbs. (0.49)	1.3 lbs. (0.59)	0.97 lbs. (0.44)	1.1 lbs. (0.49)	1.56 lbs. (0.70)

Applications

- Intake Manifolds
- Hood and fenders
- Transmission oil pans
- Water pumps
- Alternators
- Brake calipers
- Brake caliper brackets
- Lawn mower engines
- Engine brackets
- Bumpers
- Transaxle mount
- EGR valves
- Torque converters
- Fuel tank brackets
- Mud flaps



Related Items

- 207IMDFMYA Metric Impact Sockets
- 207IMDFY SAE Impact Sockets
- YA502M Swivel Connector
- IM2002A 5 ft. Whip Hose



* = All data from published specification for each product.