



ECO *plus*

ECO Plus A/C Recycler...Now with extra-long 135” hoses, which come in handy for Heavy-duty applications

EEAC324B recovers, recycles, evacuates, leak tests and recharges R-134A systems quickly and accurately. Integral oil change function and oil capture.

Fully Compliant with SAE J-2788 Standard



Features and Benefits:

- 95% Recovery efficiency, saves money on refrigerant.
- +/- 1/2 ounce charge accuracy, reduces a/c repair call-backs.
- Semi-automatic A/C Recycler.
- Microprocessor-controlled operation.
- True single-pass recycling system.
- Simple, menu-driven operation with prompts and button controls.
- Automatic high pressure shutoff.
- Automatic tank full shutoff.
- User-selectable languages - English, Spanish, French - for multilingual work force.
- Filter Life Monitor - alerts user when maintenance is needed.
- Process-Complete Notification.
- Vacuum Pump included.
- Rust-free, dent-free cabinet.

Compare EEAC324B with our major competitors:

- Two Year Warranty - An extra year**
- Built-in oil injection**

ECO Plus + Technical Support 1-866-769-2788

Country of Origin – United States



EEAC324B – ECO Plus Air Conditioning Recycler
CE – Not Available





EEAC324B – ECO Plus Air Conditioning Recycler

Specifications:

Dimensions.....34"D x 46"H x 24" W
 Power.....120 VAC, 60 Hz 12 amps maximum
 Shipping weight.....235 lbs. (107Kg)
 Operating Temperature Range.....50-120° F (10-49° C)
 Relative Humidity.....Up to 80% non-condensing
 Maximum Operating Pressure.....450 psi
 Storage Temperature Range.....4-140° F (-20 to 60° C)
 Compressor.....1/3 hp 1.1 CFM reciprocating
 - Vacuum.....28 in Hg at sea level
 Vacuum Pump.....1/4 hp 1.5 CFM reciprocating, 40 microns
 Gauge Ranges.....
 - High Side.....max. 500 psi (34BAR)
 - Low Side.....max. 350 psi (24BAR)

Capacities:

Maximum Recovery Amount: 0-23 lbs. (10.43 kg)
 Maximum Recovery Rate: 1 lb/min
 Maximum Charge Amount: 0-22 lbs. (9.98 kg)
 Onboard Refrigerant Capacity: 30 lbs. (14 kg)
 Charge Oil Bottle: 12 oz. (360 ml)
 Drain Oil Bottle: 12 oz. (360 ml)

Additional Sales Information:
 ECO Plus Bid Spec – **SS2983**
 ECO Plus Flier **SS2984B &**
DVD SS2985

Standard Parts/Accessories for EEAC324B and EEAC325B:

- EEAC325A1** - Filter Dryer, Pin-on
- EEAC325A2** - High Side Service Hose
- EEAC325A3** - Low Side Service Hose
- EEAC325A4** - Bottle, Oil Drain, Inject
- EEAC325A5** - High Side Service Coupler
- EEAC325A6** - Low Side Service Coupler
- EEAC325ACV** - Nylon Cover

Be sure to keep extra EEAC325A1 filters on hand, since new SAE standard require filter replacement after 150 lbs. of refrigerant used. Filter life prompt occurs when two-thirds of filter capacity is consumed. Mandatory filter lockout will occur after 150 lbs. of refrigerant has been used.



WARNING

•Pressurized systems can leak.



Wear safety shield.

A pressurized leak can cause eye injury.



•Pressurized fluid stream can create flying particles & can penetrate body.

Wear safety shield & protective clothing.

Do not direct air or fluid stream at body.



Flying particles, air or fluid entering the body can cause injury.

•Pressurized air or fluid stream can create dust.



Wear protective mask.

Use in well ventilated area.

Inhaling dust can cause injury.