



Snap-on® Performance LED Flashlights Really Shine in Red Anodized Finish

**ECF900R
SERIES**

Features and Benefits

- Machined Aluminum Reflectors for optimal thermal management and beam projection
- Stainless steel head protects the optical system
- High-powered 50,000 hour LEDs
- Electronically controlled for uniform light output
- Precision machined aluminum bodies – made from solid aluminum with high grade red-anodized finish
- Impact resistant- shockproof, crushproof, and water resistant
- 3 position end-cap switch – activates constant and momentary HIGH and LOW power settings, and lockout mode
- Limited Lifetime warranty



ECF900R

CE – Not required

See pages 2 through 4 for additional styles and details

Country of origin: China



- 53 Lumens Light Output from an efficient 50,000 hour LED
- Uses 1-AAA Alkaline -- provides 1 Hour, 20 minutes on High, 26 hours on low
- Effective Range 190 ft. (58 Meters)
- IPX4 rated for water resistance



ECF900R



ECF925CR

- 31 Lumens Light Output from an efficient 50,000 hour LED
- Uses 2-123A Lithium Alkaline -- provides 17 Hours, 30 minutes on High, 85 hours on low
- Effective Range 131 ft. (40 Meters)
- IPX4 rated for water resistance



- 55 Lumens Light Output from an efficient 50,000 hour LED
- Uses 1-AA Alkaline -- provides 1 Hour, 45 minutes on High, 40 hours on low
- Effective Range 266 ft. (81 Meters)
- IPX4 rated for water resistance



ECF950BR



ECF965CR

- 150 Lumens Light Output from an efficient 50,000 hour LED
- Uses 2-AA Alkaline -- provides 1 Hour, 10 minutes on High, 60 hours on low
- Effective Range 443 ft. (135 Meters)
- IPX4 rated for water resistance



- 200 Lumens Light Output from an efficient 50,000 hour LED
- Uses 2-123A Lithium Alkaline -- provides 3 Hours High, 40 hours on low
- Effective Range 636 ft. (194 Meters)
- IPX7 rated for water resistance
 - **higher immersion rating**



ECF975BR

- 227 lumens maximum light output
- 3.7 volt, 2200 mAh Lithium Ion Rechargeable Battery, AC wall charger, and DC Car Charger utilizing USB charge cable is included
- Focused spot with flood beam
- 2.75 hours run time at full power, 41 hours run time at low power
- IPX4 rated for water resistance



ECF985R





Specifications

Part #	Description	Length	Weight
ECF900R	DUAL MODE 1AAA FLASHLIGHT	2-7/8"	0.19 lb
ECF925CR	1 AA 55 LUMEN FLASHLIGHT	3-7/8"	0.25 lb
ECF950CR	56 LUMEN 5 LED FLASHLIGHT	4-3/4"	0.54 lb
ECF965CR	2AA 150 LUMEN FLASHLIGHT	5-7/8"	0.62 lb
ECF975BR	200 Lumen Flashlight	6"	0.66 lb
	227 LUMEN RECHARGEABLE*		
ECF985R	TACTICAL FLASHLIGHT	6-1/4"	0.67 lb



ECF985R Charger is CSA® and UL® approved



WARNING

Wear safety goggles (user and bystander)
Avoid looking directly into the beam
Do not use the lamp near an open flame
Always fully charge to extend battery life
Read additional safety warnings on pages W1 to W4 in Catalog 1200