

Compact 6-drawer cart for maximum performance where space is tight

KRSC326 Series

32" Wide 6-Drawer Cart

Features and Benefits

- **Higher function bumper system** on all four corners are strong and comfortable enough to be used as handles, yet soft surfaces are welcomed when approaching customer vehicles. (The corner protectors also send a professional message with high-impact logos)
- Comes fully assembled from the factory including bumpers, casters and aluminum drawer trim.
- Fully- welded double side walls
- Extra deep top compartment 7" deep for a wide range of uses such as battery storage/charging, plus it will hold a 36" pry bar handle vertically.
- Internal drawer release A flip lever in the top compartment allows drawers to open when the top compartment is closed so you can use the drawers while also using the top work surface.



See page 2, 3 and 4 for more features and benefits, stock number listing with colors, related product for customization, specifications and warnings.

Country of Origin – Canada





More Features and Benefits

- Drawers are 28" wide
- Stronger lock and cam round key lock for interchangeability and larger cam for security
- Snap-on paint and steel standards uses fully welded double sidewalls, the same paint and construction steel as Snap-on tool boxes. Made in North America
- Snap-on KRA-style drawers with lock 'n roll – helps keep drawers from drifting open
- Snap-on lifetime warranty on all parts
- Snap-on drawers and trim are a color match to our tool boxes
- Thoroughly tested rigorous bump track testing has proven the Snap-on cart lasts longer

Stock Numbers and Colors

KRSC326 - Red

KRSC326PC - Gloss Black

KRSC326PCM - Royal Blue

KRSC326PDG - Midnight Blue

KRSC326PES – Ultra Yellow

KRSC326PJH - Candy Apple Red

KRSC326PJJ - Extreme Green

KRSC326PJK - Electric Orange





KRSC326

Specifications

Overall: 16,847 cu. ln., 3,533 square inches

Drawers: (5) – 17.5" D x 27.1" W x 3.6" H (internal dimensions)

(1) – 17.5" D x 27.1" W x 7.5" H (internal dimensions)

Top Compartment: 19.6" x 32" x 6.7" (including 2 screwdriver/pry bar storage sections)

Overall Dimensions:

32.7" Width

20.5" Depth

43" Height

Related Product...to customize

Create the ultimate shop cart:

- •KRSC404APV side adaptor plate has slots to mount accessories
- •KRA4830* end cab comes equipped with adjustable shelves, optional drawers can also be added.
- •KRA4820D* six drawer end cab
- •KACSC30PC protective nylon cover
- •6007J0120PV* cord wrap, flips over for use as can holder
- •KAS12PWRPV* power tool rack (holds 3 tools)
- •KAS12PV* 12" flat shelf
- •KALR12PV* literature rack (12" wide 9" deep)
- •KAT12PV* 12" can rack (12" wide 3" deep)
- •**EEDMRACKM** magnetic side rack for electronic leads
- •KAPS4 power strip can be mounted inside top compartment
- *Requires KRSC404APV adaptor kit for mounting





KRSC326



WARNINGS

Units can tip or strike you.



•Do not open more than one loaded drawer at a time. Keep children away.





•Close lid and lock drawer and doors before moving.



•Apply brakes on locking casters when not moving unit. •Do not step in or on drawers.



•Secure units together with fasteners.




 •Read instruction Manual. Tipping of storage unit or unit striking you can cause injury.

Unit's edges can cut or pinch.




•Do not pull; push to move.





•Keep feet and fingers clear of edges when stacking,



Unit edges can cause injury.





Risk of tripping.

•Do not use extension cords with power drawer outlets.

Tripping can cause injury.



Risk of electric shock and fire.

- •Do not remove the ground connection.
- •Do not expose to rain, snow, or wet conditions.
- •Do not operate with damaged cord or plug.
- •Replace damaged cord or plug immediately.

Electric shock or fire can cause injury.



Risk of explosion.

- •This equipment should not be located in a recessed area or below floor level.
- •Flammable fuel or vapors can ignite.
- •Power drawer has internal arcing or sparking parts.
- •Do not expose to flammable vapors.
- •Power drawer components to be mounted at least 460mm (18 inches) or more above the floor.

Explosion or flame can cause injury.

