

PBC42B

Design and Smaller Footprint

Features and Benefits

- Blasts parts clean and degreases parts in less time than other methods
- Cleaning wand sprays high pressure cleaning solution and easily cleans blind holes and crevasses
- Internal heater increases cleaning solution effectiveness and helps loosen up dirt and grime
- Includes a timed automatic soak cycle that sprays cleaning solution over parts
- Removable 12 gallon reservoir features internal baffles to keep debris away from intake filter and minimizes clogs
- Automatic soak cycle is on a 0-60 minute timer allowing the user to perform other tasks



Country of origin: USA



PBC42B



Pump Motor Reservoir

Additional **Features and Benefits**

- Heater is thermostatically controlled and maintains the cleaning solution at 120 degrees
- Internal screen filter with contaminant trap to separate oil and grease from soap solution
- Includes 25 lbs. of YADW896B powdered soap for 8 complete reservoir fills

Additional Model

PBCH42B-EUR 220VAC 50Hz – CE approved

WARNINGS



•Wear safety goggles. (User and bystanders)



•Do not direct air or fluid stream at body



•Do not expose solvent to flames, sparks or other sources of ignition.



Use in well-ventilated area.



•Do not use washer without fusible link or safety valve intact.

•Read additional safety precautions on pages W1 to W4 in product catalog CAT1200.

Specifications

Pump Motor			3/4 hp
Electrical Requirements		230V AC, 60Hz	
Heater			1500 watts
Output Pressure			500psi
Volume			180 gal/hr
Reservoir Capacity	y —		12 gal
Depth			24 inches
Open Height	Y	T	69 inches
Inside Dimensions (inches)		16 to 26 H x 40 W x 24 D	
Overall Dimensions(inches)		45.5 W X 66 H x 39 D	





