



PRODUCT ANNOUNCEMENT: #19161  
DATE: APRIL 5, 1999  
CATALOG 400 INSERT AT: PAGE E45

FILE INDEX: 31.1  
ACT725



**Snap-on®**

ACT725

## **Leak D'Tector** Automatic Halogen Leak Detector

Design certified by MET  
Laboratories, Inc. to meet SAE J1627  
for R134a, R12, and R22

*Innovative circuitry with Advanced  
Digital Signal Processing monitors the  
sensing tip 2,000 per second*

### **Features**

- Microprocessor controlled circuit with Advanced Digital Processing
- Visual leak size indicators
- Detects all halogenated refrigerants
- Variable frequency audible alarm
- Mute
- True mechanical pump
- Keypad control
- One touch reset
- Non-conductive coating on tip prevents shorts
- Orange tip for enhanced visibility
- Rubber grip
- Constant power indication
- Cordless portability
- Flexible, stainless probe with clip
- Spare sensing tip included
- Optional reference leak source
- Three year limited warranty



#### **WARNING**

- Pressurized/flammable fluids and gases.

**Wear safety shield.**



**Wear protective clothing.**

**Make sure there is adequate ventilation.**

**Avoid sparks and flame.**



*Pressurized/flammable fluids and gases can cause injury.*

- Electrical shock can result while testing near electrical equipment.



**Use only nonconductive extensions while testing near electrical equipment.**



**Maintain safe distance between yourself and electrical equipment being tested.**

*Electrical shock can cause injury.*



- Moving components can cause flying particles or result in entanglement.

**Wear safety shield.**



**Maintain safe distance between yourself and moving components.**

*Flying particles and entanglement can cause injury.*

### **Specifications:**

Power Supply .....	3V DC; Two "C" Alkaline Batteries
Ultimate Sensitivity .....	Less than 0.25 oz/yr (7 gr/yr) for all halogen based refrigerants
Sensing Tip Life .....	Approximately 20 hours
Operating Temperature .....	30° to 125°F (0° to 53°C)
Battery Life .....	Approximately 30 hours
Duty Cycle .....	Continuous
Response Time .....	Instantaneous
Reset Time .....	One second
Warm-Up Time .....	2 seconds, approx
Fixed Probe Length .....	16" (40.6cm)
Overall Dimensions .....	9" x 2.5" x 2.5" (22.9 x 6.5 x 6.5cm)
Weight .....	1.2 lbs (560 grams)

© 1999 Snap-on Tools Company Kenosha, WI  
PRINTED IN U.S.A.

Copying permitted for Snap-on customers only.  
SALES COMMUNICATIONS DEPARTMENT

+Stock		+List	+Price	Weight
<u>Number</u>	<u>+Description</u>	<u>Price</u>	<u>Group</u>	<u>LBS/(KG)</u>
ACT725	Leak Detector	\$249.95	D	2.0/(9.1)

\* \* \* \*

Sales Material:	Front Page of this Sheet
Family Code:	00NA20990990
Commodity Code:	9031800060
Parts Reference:	To follow
Branding/Product:	Blue-Point
Branding/Package:	Blue-Point
Available for Export:	Yes
Country of Origin:	USA
Warranty Code:	L3
+Inventory Class:	1
+Order Point:	“ ”
Field Assembled Sets Affected:	None

+ Fields for DSS Data Entry

---