6000 lb SCISSORS LIFT EELR300A EELR301A

Electric Motor

115V, 3/4 HP

Air Motor

100PSI

SPACE SAVING SCISSOR LIFT DESIGN lifts straight up -- no fore or aft movement.

37" LIFT HEIGHT TRAVEL facilitates body work, tire, wheel, or brake service.

THIS PORTABLE (OR FIXED INSTALLATION, IF YOU WISH) UNIT will go to the job -- use it outside on a solid level surface. Twelve feet of hose & quick-disconnect are standard equipment. Power Pack doubles as a Tow Cart allowing the unit to be easily moved.

Low 4-3/4" DRIVE OVER HEIGHT allows the unit to be slipped under a disabled vehicle.

Frame contact or pad lift allow use with a wide range of vehicles.

DUAL SAFETY SYSTEM features a mechanical lock & hydraulic velocity fuse.

SPECIFICATIONS:

| Down Position Height 4 ³ / ₄ " | Full Lifting Height 37" |
|--|------------------------------|
| Overall Length (lowered) 75 " | Overall Width (with arms in) |
| Opening in mid-frame 14" | Electric Motor115V, 3/4 HP |
| Air Motor 100 PSI | Lifting Time |
| | Shipping Weight 950 lbs. |

OPTIONAL ACCESSORIES: _____

Frame Contact Lift Blocks (4) EELR313A Truck Extensions (2) EELR314A




WARNING

Improperly lifted vehicles can fall

- do not use a damaged lift
- use only on a solid & level surface
- do not let passengers occupy vehicle
- pick up vehicle by proper load points
- avoid excessive rocking of the vehicle
- use auxiliary supports when removing a heavycomponent
- clear area if vehicle is about to fall Improperly loaded lift can collapse
- do not use a damaged lift
- do not exceed rated capacity
- do not use adaptors that reduce rate capacity Improperly operated lift can crush you

operate only if trained



- stay clear of lift with body during raising or lowering lift & vehicle
- do not move portable lift while loaded with
- check for positive engagement of mechanical lock device prior to going under vehicle or lift
- use auxiliary supports, jackstands with proper load rating
- read & follow instruction manual

Improperly operated & improperly loaded lift can cause injury





© 1996 Snap-on Tools Company Kenosha, WI Copying permitted for Snap-on customers only SALES COMMUNICATIONS DEPARTMENT

Product Announcement: #18464 — Page 2 — File Index: 31.0 Date: June 3, 1996 EELR300A & EELR301A

| +Stock | | +List | +Price | Weight | |
|-----------------------------------|-------------------------------|--------------|-----------------|------------|--|
| <u>Number</u> | +Description | <u>Price</u> | <u>Category</u> | LBS/(KG) | |
| | | | | | |
| EELR300A | Scissor lift, Electric | \$ 2,850.00 | M | 950/(431) | |
| EELR301A | Scissor lift, Air | \$ 3,250.00 | M | 950/(431) | |
| EELR313A | Frame Contact Lift Blocks (4) | \$ 110.00 | M | 15.0/(6.8) | |
| EELR314A | Truck Extensions | \$ 125.00 | M | 13.0/(5.6) | |
| (Price does not include shipping) | | | | | |

* * * *

Sales Material: See front of this letter; SPP812, Wheeltronic Binder;

SV294, EELR300A Flyer; SPP811, Wheeltronic Prop Set

Parts Reference: None
Dealer Stock Order Form: Yes
RPC Replacement: No

Branding/Product: Snap-on & Stock No. Branding/Package: Snap-on & Stock No.

Available for Export: Yes
Country of Origin: Canada

Warranty Limited to: EELR300A & EELR301A = 1 Year Parts & labor

+Inventory Class:

+Order Point:

Field Assembled Sets Affected: None

+ Fields for DSS Data Entry