

BK3000

Video Inspection Scope


Easy to Use, Versatile Imager Covers all the Basics

Features and Benefits

- Small, rugged package designed for comfort and functionality with vibrant 2.5" LCD screen
- Integrated 8.5mm high-res imager allows for ease of use and ensures the product is always ready-to-go
- On-board storage of up to 30 images
- Simple and user-friendly 5 key switch
- Adaptable functionality through 3-step zoom, adjustable brightness, and 180° image rotation
- Magnet and mirror accessories with integrated storage gives user additional flexibility
- Powered by AA batteries
- Imager is resistant to dust, dirt, and water ingress for 30 minutes at depths of up to 3m















⚠WARNING



· Use of diagnostic equipment on a rotating engine poses a risk of flying particles and entanglement



Wear safety goggles (User and Bystander) Use caution in routing cables

Flying particles can cause injury Poorly routed cables and test leads can cause entanglement and injury




• Use of diagnostic equipment can cause electrical shock, fire, and explosion



Use caution and proper procedures when connecting and disconnecting leads Diagnostic equipment must be located 18" or more above floor level



Avoid sparks and other sources of ignition Electrical shock, flames and explosion can cause injury





Read and follow all safety precautions accompanying the product

Unexpected electrical, thermal, or mechanical occurrences can cause injury

Read additional safety warnings on pages W1 to W4 in Catalog 1300

Specifications

Field of View Forward	54° diagonal
Operating Temp Range	30-122 °F
Optimal Focal Range	1/2-12"
Power Suppler	(4) AA Batteries
Resolution (Reading Display)	160 x 240 RGB Backlight LED
Resolution, Imager	640 x 480
Run Time (hours)	Alkaline Batteries: 4
Storage Temperature	-4-140 °F
Water Resistance, Imager only when assembled	to a depth of 10' (3 M)

