



EEBC500A

Battery Charger Plus™

12 and 24 V DC Battery Charger Plus now with 100 Amp Flash Reprogram Mode

Batteries have changed, has your charger?

Features and Benefits

- **Plus:** Exclusive flash reprogram power supply maintains consistent OEM specified voltage up to **100 Amps for 3 minutes**
- **Adaptive:** Performs a unique charge cycle for each lead acid battery type: standard, AGM, GEL or deep cycle
- **Versatile:** Charge 6, 12 and 24 Volt batteries with a 4 Amp maintain rate, a 15 Amp fast rate or a 60 Amp boost mode – in 24 V setting, the boost is 30 Amps
- **Convenient:** Upper and lower battery service tool storage trays
- **Intelligent:** Automatic microprocessor-controlled operation selects algorithm to optimize cycle without overcharging
- **Powerful:** At 12 V setting, 300 Amp engine start with **20 second** crank time



Technical Support
866-713-6007

CE - Not Available

UL US
LISTED
Indoor/Outdoor Use

BC

Country of Origin: MEXICO

Snap-on®

Snap-on is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All other trademarks are marks of their respective holders.
©Snap-on Incorporated 2017. All rights reserved.
Snap-on, 2801 80th Street, Kenosha, WI 53143 www.snapon.com

February 2017
Page 1 of 3



EEBC500A

Features and Benefits Continued

- **Informative:** In maintain and fast rate, unit displays vehicle battery voltage, % of charge and alternator % of performance
- **Streamlined:** Higher working-height handle helps relieve back strain with an excellent design that looks like no other charger
- **Tough:** 10" foam filled tires with C-CLIP retention ride on solid steel axle

Top storage area for optional battery service hand tools (2005BSK)



Related Items

EEBC500CVR Battery Charger Cover

WARNING

- Batteries produce explosive gases and can explode
Wear safety shield (User and Bystander)
Do not overcharge the battery
- **Keep flames and sparks away from the battery**
• Sparks occur when connecting or disconnecting leads while charger is ON
- **Charger must be OFF when connecting or disconnecting leads.**
Battery explosion or ignited gases can cause injury
Read and follow all safety precautions accompanying the product Unexpected electrical, thermal, or mechanical occurrences can cause injury
Read additional safety warnings on pages W1 to W4 in Catalog 1300





EEBC500A

Specifications

AC Circuit Breaker	Self-Resetting
AC Cord Gauge	14-3
AC Cord Length, feet (meters)	9 (2.7)
Continuous Input Current (Max), Amps	14.6
Country of Use	North America
Crank Assist Duty Cycle	1/36
Crank Assist Rating, ADC	300
DC Circuit Breaker	Self-Resetting
DC Clamps	500A
DC Lead Gauge	4 AWG
DC Lead Length, feet (meters)	7' 6" (2.3)
DC Lead Type	Fixed
Dimension W x D x H, inches	20 x 23 x 40

Input Voltage (Rated), VAC	120
Outdoor Use	Yes
Output Currents ADC	4/15 and 60A Boost
Output Voltages VDC	6/12/24
Power Supply Cord	Included
Rectifier	8 SCR
Timer Type	Digital
Ventilation	Fan Cooled
Voltmeter	Digital
Warranty	2 Years
Weight, lb	91.8
Wheel Size, inches (mm)	10

NOTE: Handle and wheel assembly required

