



Coolant Exchange  
**Complete automotive coolant drain & fill  
 in less than 8 minutes**

**Fast**

- Complete drain & fill in less than 8 minutes
- Easily connects to upper radiator hose with reusable hose adapters

**Easy to Use**

- Engine Off Process – All service is performed with the engine cold
- One master valve controls Drain, Test Vacuum, Flush & Fill
- Powered by shop air (30-90 psi) – No electrical hook up
- Informative user feedback provided by built-in pressure regulator, pressure/vacuum gauge & dual tank level sight glasses
- Built-in storage trays, hose wrap, & handle
- Large, 10 inch wheels & swivel casters provide mobility

**Thorough**

- Vacuum refill process eliminates air in cooling system
- Unit pressure tests the complete cooling system including the radiator cap release
- Dual storage tanks – 32 qt (30.2 liter) each
- Continuous Flush function cleans extremely dirty or contaminated systems

**Includes**

- Suction Wand Assembly: EAA0196L47AR
- Radiator Adapter Assembly (1.25"-1.38"): EAA0195L26AR
- Radiator Adapter Assembly (1.50"-1.75"): EAA0195L27AR
- Hose Pinch Pliers, Large: 8-850
- Hose Pinch Pliers, Medium: 8-950
- Hose Pinch Pliers, Small: 8-1150
- Rubber Coolant Hose, 1.25" ID: 5-4835-030
- Rubber Coolant Hose, 1.38" ID: 5-4935-030
- Rubber Coolant Hose, 1.50" ID: 5-5035-030
- Rubber Coolant Hose, 1.75" ID: 5-5135-030

**Optional Accessories**

- Recycler Kit: EAK0239L01B
  - Dual stage filtration with 20 & 5 micron cartridge filters
  - Processes up to 5 gallons per minute
  - Batch recycle using dual internal tanks
- Extended Adapter Set (2", 2.25", & 2.5"): EAK0239L02A
- 5 Micron Replacement filter: 1-12881
- 20 Micron Replacement filter: 1-12781

**Specifications**

- Pressure/Vacuum Gauge: 30 in Hg to 30 PSI
- Operating Temperature: 0° to 120°F (-17.8° to 48.9°C)
- Storage Temperature: -4° to 150°F (-20° to 65.5°C)
- Dimensions: 41.5"H x 33"W x 25.75"D
- Weight: 123 lbs (55.8 kg)
- Power: 30-90 PSI max, compressed shop air



**EESE336A**  
 Coolant Exchange


**WARNING**


• Wear safety goggles. (User &amp; bystanders)



• Read &amp; follow instructions before operating.

EU - Unavailable

©2005 Snap-on Incorporated. All Rights Reserved.

#21069

Snap-on is a trademark, registered in the United States and other countries, of Snap-on Incorporated.  
 Other marks are marks of their respective holders.

Brand Marketing

**E35**  
 Catalog 700

**FILE INDEX: 31.0  
EESE336A**

<u>+Stock</u>		<u>Superseded</u>	<u>+List</u>	<u>+Price</u>	<u>Weight</u>
<u>Number</u>	<u>+Description</u>	<u>Stk. No.</u>	<u>Price</u>	<u>Category</u>	<u>LBS/(KG)</u>
EESE336A	Coolant Exchange	EESE136C	\$2,407.50	T	123(509)
EAK0239L01B	Recycler Kit	EAK0239L01A	\$337.00	T	13.9/(6.3)
EAK0239L02A	Extended Adapter Set	n/a	\$203.00	T	5.0/(2.3)

\* \* \* \*

Sales Material: Front Page of this Sheet; Bid Spec, SS2023E;  
Trifold, SS2045C; Pocket Card, SS2046B;  
POP Bifold, SS2199B; POP Counter Card, SS2198B;  
POP Banner, SS2197B; POP Poster, SS2200B;  
POP Kit, SS2196B

Family Code, EESE336A: S0N5C0990990  
Family Code, Other: S0NAK0990990  
Commodity Code: 9031800060  
Parts Reference: To follow  
Branding/Product, EESE336A: Snap-on  
Branding/Product, Other: SUN  
Branding/Package: Snap-on  
Branding/Package, Other: SUN  
Available for Export: Yes  
Country of Origin, EESE336A: Mexico  
Country of Origin, Other: USA  
Warranty Code: 07  
+Inventory Class: 1  
+Order Point: “ ”  
Field Assembled Sets Affected: None

+ Fields for DSS Data Entry