

Blue-Point

# **Back-Tap™ Spark Plug Thread Chasers**

Starts threading at the bottom of the spark plug port

- · Avoiding potential cross threading. Most thread damage occurs at the top of the port. By starting the rethreading at the "good" threads, chances of cross threading are eliminated.
- · Filings are brought up & out of the spark plug port.

## No need to pull the cylinder head!





#### SPHR2

### **10mm** Back-Tap<sup>TM</sup>

- Motorcycles Power Equipment
- · Outboard Marine · Small Engines



#### SPHR3

## 12mm Back-Tap<sup>TM</sup>

- Import Autos Motorcycles
- Outboard Marine Small Engines
- Power Equipment



#### SPHR1

## **14mm** Back-Tap<sup>TM</sup>

Most common spark plug size



#### SPHR4

## **18mm** Back-Tap<sup>TM</sup>

• Oxygen Sensor Ports • 18mm Spark Plugs



#### WARNING

Wear safety goggles. (User & bystanders) Do not use with air tool.

© 2002 Snap-on Tools Company Kenosha, WI

Printed in U.S.A. #20148

Copying permitted for Snap-on customers only. Sales Communications Department



FILE INDEX: 2.0 SPHR2, 3, & 4

+Stock		+List	+Price	Weight
Number	+Description	Price	Category	LBS/(KG)
SPHR2	Back-Tap Hole Rethreader, 10mm	\$54.95	D	0.25/(0.11)
SPHR3	Back-Tap Hole Rethreader, 12mm	\$59.95	D	0.25/(0.11)
SPHR4	Back-Tap Hole Rethreader, 18mm	\$79.95	D	0.25/(0.11)

\* \* \* \*

Sales Material: Front Page of this Sheet;

Family Code: 00NMB0990990 Commodity Code: 8203100000

Parts Reference: N/A
Branding/Product: None
Branding/Package: Blue-Point

Available for Export: Yes
Country of Origin: USA
Warranty Code: S4
+Inventory Class: 1
+Order Point: ""

Field Assembled Sets Affected: None

<sup>+</sup> Fields for DSS Data Entry